


PRELOAD(kgf)	_____
R.D	_____
S.F (kgf)	_____
DRAG TORQUE(kgf-cm)	_____
LUBRICATION	OIL
DIRECTION OF TURN	RIGHT
PC DIA.	64.534
BALL DIA.	6.35
BACKLASH	0.15MAX
CIRCUIT	6
LEAD ANGLE	2.82°
DYNAMIC (kgf)	6192
STATIC (kgf)	21409
LEAD	10.

SPEC: R63-10T6-FSI



THREAD LENGTH 	UNCHAMFERED USE <input type="checkbox"/> C0.5 <input checked="" type="checkbox"/> C1 <input type="checkbox"/> C ROUGH M/C FIN M/C GRD 25° 6.3° 0.4g						SCALE	MATAL	NT: SNCM220	DATE
	UNTOL DIMN mm TO 6 30 120 300 600 1200 2400 ±0.1 ±0.2 ±0.3 ±0.4 ±0.5 ±0.8 ±1.0 ±1.5						1: X		DATE	12.19.'00
	*BREAK SHARP EDGE UNLESS OTHER SPECIFIED. *未量倒角者以R0.5MAX								DATE	12.19.'00

CUSTOMER DRAWING NO.	CISTR	HIWIN
DATE	DWG.NO.	
DATE	DATE	
DATE	DATE	
DATE	DATE	
DATE	DATE	
DATE	DATE	
DATE	DATE	

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

DATE	MODIFICATION	APPROVED